

# Acrylic silicon High elastic coating

## 厦光质感涂料



### 产品简介：

厦光质感涂料由高分子聚合物树脂、耐候颜料和构成纹理质感精细天然石英骨料等材料组成，具有优异的弥盖裂纹能力、附着力强、憎水透气、装饰效果贴近自然，充分展现了自然、生动、创意建筑之美。

### Product features:

Texture paint, weather resistant pigments and polymer resins constitute texture textured materials such as fine natural quartz aggregates composed of masked crack has excellent ability, strong adhesion, water repellent breathable decoration natural, full, vivid and creative architectural beauty of nature.

### 性能特点：

- 有效弥盖墙体裂纹

■ 优异的防水透气性

■ 突出的耐沾污性
- 强烈的立体质感

■ 优异的耐久性

■ 自然古朴色彩
- 附着力强

■ 纹理多样

■ 不易褪色

### Application of places

- Effectively masked wall cracks

• Superior waterproof breathable


• Excellent weather resistance
- Strong solid texture

• Excellent durability

• Natural rustic color
- Strong adhesion

• Texture variety

• Resists fading



### 适用场所：

适用于高档别墅、高档商住楼、多层公寓、酒店、办公楼、住宅小区和厂房。

### Application of places

Apply to luxury villas, apartment buildings, high-rise apartment, hotels, office buildings, residential areas and factories.

### 技术参数：

- 基料：

纯丙烯酸共聚乳液。
- 产品特征：

水溶性、薄质、彩色、厚质。
- 干燥时间：

表干12小时，重涂时间24小时，实干48小时。（温度25℃，相对湿度80%）。
- 理论耗漆量：

1.20~3.50kg/m<sup>2</sup>，实际涂布量因基面状况，施工方法、颗粒粗细不同有所差异。

### Technical parameters

- Base material:

acrylic polymer emulsion.
- Product features:

water soluble, thick paste type, flexible/flexible series.
- Drying time:

dry for 12 hours, Recoat time 24 hours, work for 48 hours. (Temperature 25℃, relative humidity 80%).
- Consumption of paint:

Coarse particle size 1.20kg/m<sup>2</sup>-size 3.50kg/m<sup>2</sup>, Practical coating by surface conditions, construction methods, particle fineness and differences.

### 施工：

- 施工方法：

批刮、喷涂、揉搓。
- 稀释比例：

一般不宜加水稀释，确因施工困难，可酌加5%以内清水稀释。
- 施工要求：

在5℃~35℃及相对湿度80%以下施工。大风、下雨等恶劣天气应避免施工。

### Technical parameters


- Construction method:

rubbing, scratching, spraying,
- Dilution ratio:

generally should not be diluted with water, because of engineering problems, may be subject to additional 5% less than clear water dilution
- Construction requirements:

5℃ ~35℃ and relative humidity below 80% construction. Construction of wind, rain and other inclement weather should be avoided.

### 典型方案 Typical scenarios：



### 平面工艺

- ① 基层：

厦光中层柔性腻子/厦光专用中层腻子2道
- ② 底漆：

厦光抗碱封闭底漆/厦光含砂专用封闭底漆1道
- ③ 主材：

厦光质感涂料1~2道
- ④ 罩面：

厦光罩面涂料1道
- ① The grass-roots level:

Light Middle flexible Putty/Terminal special Putty for middle-level 2
- ② Primer:

alkali-resistant primer/HA HA light light sand special primer 1
- ③ Main material:

texture paint light 1~2 road
- ④ Overlay:

overlay coatings 1



质感——赋建筑以生动之美  
Texture - construction endowed with vivid beauty



工艺——赋建筑以创意之美  
Process - Fu beauty of the building creative



色彩——赋建筑以自然之美  
Color - Fu building natural beauty